In the Claims:

This listing of claims replaces all prior versions, and listings, of claims in the application.

- 1. (Currently Amended) A vacuum cleaning head comprising a housing, an agitator for agitating a floor surface, a chamber disposed in the housing for rotatably receiving the agitator, an opening formed in a portion of the chamber adjacent the agitator facing a floor surface, an air turbine driving the agitator, an air inlet in the housing admitting clean air to drive the turbine, a restricting device fitting in a discharge outlet from the chamber, the restricting device being configured so as to be movable between a restrictive position, in which [[it]] the restricting device serves to restrict the cross-section of the discharge outlet, and an open position, in which [[it]] the restricting device restricts the cross-section of the discharge outlet to a lesser extent, the restricting device being movable by the flow of debris from the chamber.
- (Original) A vacuum cleaning head according to claim 1, wherein the restricting member comprises a guide vane which projects outwardly from a wall of the discharge outlet.
- (Original) A vacuum cleaning head according to claim 2, wherein the guide vane is resiliently biased into the restrictive position.
- (Previously Presented) A vacuum cleaning head according to claim 3, wherein the guide vane is connected to the wall of the discharge outlet by a resilient member.
- (Original) A vacuum cleaning head according to claim 4, wherein the resilient member is a spring.
- (Previously Presented) A vacuum cleaning head according to claim 4, wherein the guide vane is mounted on a piece of resilient material which is secured to a wall of the discharge outlet.
- (Original) A vacuum cleaning head according to claim 6, wherein the piece of resilient material is generally wedge-shaped.
- (Original) A vacuum cleaning head according to any one of claims 2 to 7, further comprising a shielding member for shielding the space beneath the guide vane.

- (Original) A vacuum cleaning head according to claim 8, wherein the shielding member is a piece of compressible material which fits beneath the guide vane.
- (Currently amended) A vacuum cleaning head according to claim 9, wherein the compressible material is a foam or a foam-like-material.
- 11. (Previously Presented) A vacuum cleaning head according to any one of claims 2 to 7, wherein the downstream end of the guide vane is connected to the wall of the discharge outlet by a flexible member.
- 12. (Original) A vacuum cleaning head according to claim 11, wherein the guide vane and flexible member are formed integrally with one another from a resiliently flexible material.
- (Previously Presented) A vacuum cleaning head according to any one of claims 2 to
 further comprising a plurality of restricting devices arranged across the discharge outlet.
- 14. (Previously Presented) A vacuum cleaner comprising a vacuum cleaning head according to any one of claims 2 to 7.
 - 15. (Canceled)
- 16. (Previously Presented) A vacuum cleaning head according to claim 4, wherein the guide vane is formed from an exposed surface of a piece of resilient material which is secured to a wall of the discharge outlet.
- 17. (Previously Presented) A vacuum cleaning head according to claim 16, wherein the piece of resilient material is generally wedge-shaped.